

GENERAL NOTES:

- INTERIOR PARTITIONS SHALL BE 200 MM CMU UNLESS NOTED OTHERWISE.
 SURFACES TO BE PAINTED SHALL BE CLEAN AND FREE OF FOREIGN MATTER BEFORE APPLICATION OF PAINT. CLEANING SHALL BE SCHEDULED SO THAT DUST AND OTHER CONTAMINANTS WILL NOT FALL ON WET, NEWLY
- CONCRETE AND INTERIOR MASONRY SURFACES GROUTED SOLID SHALL BE ALLOWED TO DRY AT LEAST 30 DAYS BEFORE PAINTING EXCEPT CONCRETE SLAB ON GRADE WHICH SHALL BE ALLOWED TO CURE 90 DAYS BEFORE PAINTING.
- PAINTS CONTAINING LEAD IN EXCESS OF 0.06 PERCENT BY WEIGHT OF THE TOTAL NONVOLATILE CONTENT SHALL NOT BE USED.
- MERCURIAL FUNGICIDES SHALL NOT BE USED IN OIL—BASE PAINT.
 REMOVE LOOSE DIRT AND CLEAN SURFACES BEFORE PAINTING. APPLY PAINT TO INTERIOR STRUCTURAL RIGID FRAMINGS AND CEILINGS AND TEST FOR ADHESION. PRIMER COAT FOR MASONRY. INITIAL FIRST COAT WITH AN ACRYLIC LATEX PAINT FOR EXTERIOR SURFACES AND A SECOND COAT WITH A WATER REPELLENT ACRYLIC
- METAL DOORS AND FRAMES SHALL RECEIVE A PRIMER COAT PLUS TWO COATS OF PAINT.
- DIMENSIONS ARE TO STRUCTURAL COLUMN GRID, EDGE OF WINDOW OPENINGS, AND TO HINGE SIDE OF DOOR OPENINGS
- ALL SHOWER STALL DOORS SHALL BE F.1.5 UNLESS NOTED OTHERWISE. SEE A5 FOR DOOR/FRAME AND HARDWARE TYPES
- ALL TOILET STALL DOORS SHALL BE T.1.5 UNLESS NOTED OTHERWISE. SEE A5 FOR DOOR/FRAME AND HARDWARE TYPES.
- INSTALL SHOWER CURTAINS AND RODS AT ALL SHOWERS.
- SEE PLUMBING DRAWINGS FOR FLOOR DRAIN LOCATIONS.
- PROVIDE CERAMIC TILE AT ALL SHOWER PANS AND SHOWER SURROUNDS.
- PROVIDE CERAMIC TILE AT ALL ABLUTION AREAS PANS AND SURROUNDS.
- SLOPE 1500 MM AREA AROUND DRAINS DOWN TO DRAIN AT 1:50 SLOPE. DRAIN SHALL BE SITUATED 30MM

 \otimes

PAINTED PLASTER.

SEALED CONCRETE PAINTED PLASTER APPLIED TO STRUCTURE

2400 MM HIGH CERAMIC TILE WAINSCOT, PAINTED PLASTER ABOVE WAINSCOT WALLS:

FLOOR: CERAMIC TILE CEILING: PAINTED PLASTER

KEY NOTES:

- 1. TYPICAL TOILET STALL LAYOUT RE: DETAIL 1/A6
- 2. CONCRETE STOOP RE: DETAIL 7/A5
- 3. SHOWER CURTAIN AND CURTAIN ROD, TYP. AT EACH SHOWER
- 4. FLOOR DRAIN, TYP
- 5. (7) STAINLESS STEEL LAUNDRY TUBS

LEGEND:

- DOOR TYPE, SEE SHEET A5
- KEY NOTE
- FIRE EXTINGUISHER CABINET
- WINDOW TYPE, SEE SHEET A5
- ROOM FINISH TYPE DESIGNATION
- FLOOR DRAIN

UNLESS OTHERWISE NOTED, LINEAR DIMENSIONS SHOWN ARE IN MILLIMETERS (MM)



REFERENCE NUMBER: Α1

US Army Corps of Engineers Afghanistan Engineer District

HAH



MA

FLOOR PLAN AND ENLARGED PL STANDARD DESIGN FOILET ABLUTION BUILI